

Operation & Maintenance Instructions

Operation: Load shelves with items evenly distributed on the shelf.

Maintenance:

1. To remove dirt or grime; use a mild soap or cleanser (no abrasives). If there is any question as to suitability, test a small area on an inconspicuous part of the shelving to insure there will be no damage to the finish. Rinse to remove any residue if necessary. Do not "hose down" shelving. Dry shelving thoroughly. Do not leave liquid (or drops) on any surface.
2. Tighten all loose hardware.
3. Replace any badly worn or broken parts.



1" x 2³/₈" uprights (13 gauge), are the largest anywhere. Side embossing adds even more strength and rigidity to the unit.

Iron Grip studs allow adjustment of shelves instantly on 11¹/₂" centers.

Front and rear shelf flanges extend around the sides past keyhole. Steel stud binds both flanges to upright.

Dividers adjust on 1" centers with Speedy clips on 36" wide shelving (3" centers on 48" widths).

Shown in color for clarity, parts are actually zinc plated.

Iron grip key
Fasten any two shelving units together quickly and easily. Easy-access keys remove just as simply, allowing rearrangement of any unit without disturbing adjacent units.
U.S. patent No. 2,824,775

Use Iron Grip shelving in a variety of configurations: free-standing; side-by-side; back-to-back; or arranged in efficient work centers. Each shelf unit has four uprights.

Open shelf

EQ #2823, Metal Shelving
Equipto #64W6, 48"W x 24"D x 84"H
190330A, footplates (front)
190335A, footplates (rear)

For LSI
By Chris Bruce
7/31/2009

#5158-6M

InnerSpace
ENGINEERING CORPORATION
Ph: 650/341-7700 Fax: 650/341-0244
<http://www.InnerSpaceEng.com>

San Quentin State Penitentiary :Project
Central Health Services Bldg. :Site
Miscellaneous Equipment Items :Scope
#2823 by Equipto

Operation & Maintenance Instructions

Operation: Load shelves with items evenly distributed on the shelf.

Maintenance:

1. To remove dirt or grime; use a mild soap or cleanser (no abrasives). If there is any question as to suitability, test a small area on an inconspicuous part of the shelving to insure there will be no damage to the finish. Rinse to remove any residue if necessary. Do not "hose down" shelving. Dry shelving thoroughly. Do not leave liquid (or drops) on any surface.
2. Tighten all loose hardware.
3. Replace any badly worn or broken parts.



EQ #88, Convertible Linen Trux
Metro #CLTS2460C, 28"W x 48"D x 68"H

For LSI
By Chris Bruce
7/31/2009

#5158-7M

InnerSpace
ENGINEERING CORPORATION
Ph: 650/341-7700 Fax: 650/341-0244
<http://www.InnerSpaceEng.com>

San Quentin State Penitentiary :Project
Central Health Services Bldg. :Site
Miscellaneous Equipment Items :Scope
#88 by InterMetro